

1. What would be the output of the following MIPS code?

```
.globl main
main:
    addu    $s7, $0, $ra
    add    $s3, $0, $0
    addi   $s4, $0, 1
    add    $s5, $0, $0
    la     $s6, save

    .data
    .align 2
    .globl save

# the next line creates an array of 10 words that can be referred to
# as "save"
# the array is initialized to the 10 values after .word
# so the first array entry is a 0 and the last entry is a 2
save: .word 0, 0, 0, 0, 0, 0, 0, 0, 6, 3, 2

.text

Loop:
    add    $t8, $s3, $s3
    add    $t8, $t8, $t8
    add    $t8, $t8, $s6
    lw     $t9, 0($t8)
    bne   $t9, $s5, Exit

    add    $s3, $s3, $s4
    j     Loop

Exit:
    .data
    .globl message1
message1: .asciiz "\nThe value of i is: "
    .text
    li     $v0, 4
    la     $a0, message1
    syscall
    li     $v0, 1
    add   $a0, $0, $s3
    syscall

    addu   $ra, $0, $s7
    jr     $ra
    add   $0, $0, $0
```

2. The following code fragment computes the Kronecker product of two matrices – don't worry if you have never heard of Kronecker – this problem assumes no foreknowledge of this, as you can discern what is being done by examining the code. The matrices  $a$  and  $b$  are the input matrices – and  $c$  is the output matrix – note that  $c$  is larger:

```
#define SIZE 40
#define KSIZE SIZE*SIZE

int a[SIZE][SIZE];
int b[SIZE][SIZE];
int c[KSIZE][KSIZE];
```

The actual product can be computed as follows (with somewhat inefficient code):

```
for (i=0; i<SIZE; i++)
    for (j=0; j<SIZE; j++)
        for (x=0; x<SIZE; x++)
            for (y=0; y<SIZE; y++)
                c[i*SIZE+x][j*SIZE+y]=a[i][j]*b[x][y];
```

The choice of loop ordering is, as always, important here for memory performance. In this case, there are four nested loops – and this code is written in such a way that there are no dependencies to impede reordering. The code is shown with ordering  $ijxy$  (i.e. the ordering of the loops from inner to outer – as labeled by the iterator of the loop). Which of the following orderings should be the *worst* for this loop? By worst, we mean the ordering which will result in the *longest* execution time.

- a. ijxy
- b. jixy
- c. xiyj
- d. ixjy
- e. jyix